

ZXE15S4

Power Handling
350 Watts RMS / 700 Watts Max.

Technical Specifications

Impedance	Zn	4 Ohms
Voice Coil Diameter	Ø	64 mm
Voice Coil Winding Height		15 mm
Max. Linear Excursion	Xmax	+/- 3,5 mm
Max. Mechanical Excursion	Xmax (Peak)	+/- 19 mm
Cone Area	Sd	844 cm²
Moving Mass	Mms	181 g
DC Resistance	Re	3,6 Ohms
Resonance Frequency	Fs	34 Hz
Mechanical Q-Factor	Qms	3,95
Electrical Q-Factor	Qes	0,68
Total Q-Factor	Qts	0,58
Equivalent Air Volume	VAS	121 L
Flux Density	B/L	12,69 N/A
Efficiency 1W/1m	SPL	91 dB

Single Voice Coil
Subwoofer 38 cm

Recommended Enclosure

Sealed Box
 Sealed Volume: 60 - 120 L
 -3 dB Rolloff (F3): 42 Hz

Compact

Recommended Enclosure

Ported Box
 Vented Volume: 90 L
 Port Diameter: 2 x 100 mm
 Port Area: 160 cm²
 Port Length: 30 cm
 Tuning Freq. (Fb): 35 Hz
 -3 dB Rolloff (F3): 36 Hz

Deep Tuning

Mechanical Components

- Steel Basket
- Non-pressed Paper Cone
- Foam Surround
- Injected PP Dustcap
- Single Polycot Spider
- Y35 Magnet 56 oz (1.588 g)
- Magnet Size: Ø156 x 20 mm
- Aluminium Voice Coil Former

Dimensions & Weight

External Diameter: 395 mm
 Mounting Diameter: 360 mm
 Mounting Depth: 165 mm
 Shipping Weight: 0,0 kg

